HiSEAL™ Valves

Valve Configuration Form
4000100-0
April 2019

Basic Configuration Data
All fields must be completed

Valve Size: ANSI Class: Flow Media:

Maximum Operating Pressure: Service Temperature Range: to

Material Specifications
Please define material specifications. If no material specifications are expressly required, write 'N/A'

Body: Seat: Ball: Stem:

Construction Specifications
All fields must be completed

Port: (Choose One)
- ☐ Reduced Port
- ☐ Full Port

Ball: (Choose One)
- ☐ Floating Ball
- ☐ Trunnion Mounted Ball

Body: (Choose One)
- ☐ Fully-Welded
- ☐ 2-Piece Bolted
- ☐ 3-Piece Bolted

Environment: (Choose One)
- ☐ Above-Ground
- ☐ Below-Ground : Stem Height

Factory-Installed Pups: (Choose One)
- ☐ No
- ☐ Yes*, Length:

*Uncoated Distance from End:

End Connection: (Choose One)
- ☐ Weld×Weld
- ☐ Weld×Flange ☐ Raised-Face Flange
- ☐ Flange×Flange ☐ Raised-Face Flanges
- ☐ Other:

☐ *Length Specification: (Choose One)*
- ☐ API 6D
- Other:

Line Connection: (Choose One)
- ☐ Line Pipe Specification:
- ☐ Line Pipe OD:
- ☐ Line Pipe Thickness / Schedule:

Operator: (Choose One)
- ☐ 2" Square Nut
- ☐ Curb Nut
- ☐ Lever
- ☐ Gear Operator With:
  - ☐ Horizontal ☐ Hand Wheel ☐ 2" Nut
  - ☐ Vertical ☐ Hand Wheel ☐ 2" Nut
- ☐ Electric Actuator
- ☐ Pneumatic Actuator
- ☐ No Gear (Bare Stem)

Design: (Select Desired)
- ☐ Fire Safety
- ☐ Double-Piston
- ☐ Double Block & Bleed
- ☐ Anti-Static Devices
- ☐ Double Seats
- ☐ Locking Flange
- ☐ System Vent / Drain / Sealant Ports:

Vent:	*Drain:*	*Sealant:*
☐ Plug	☐ Plug	☐ 1 Check Valve
☐ Ball Valve	☐ Ball Valve	☐ 2 Check Valve
☐ Relief Valve	☐ Relief Valve	☐ Extension*
☐ Extension*	☐ Extension*	

*Extension Length: V D S

Certifications / Testing / Coating
All fields must be completed

Certification: (Select Desired)
- ☐ API 6FA
- ☐ API Q1
- ☐ Other:

Test Standard: (Choose One)
- ☐ API 598
- ☐ Other:

Additional Testing:
- ☐ Fire Safety
- ☐ Anti-Static
- ☐ NDT:
- ☐ Third Party to Witness
- ☐ Other:

Paint / Coating: (Choose One)
- ☐ MFG Standard
- ☐ Other:

Thickness: mils

☐ *Packaging Spec: (Choose One)*
- ☐ MFG Standard
- Other:

Other Requirements / Notes:

Marking: (Choose One)
- ☐ MFG Standard
- ☐ API 6D
- ☐ Other:

Company:
Name:
Title:
Date:
Sign:

SUBMIT

M.T. Deason Co., Inc. • 2820 Commerce Blvd. • Birmingham, AL 35210-1216 • 205-956-2266 • Fax 205-956-1911 • www.mtdeason.com
Data subject to change without notice. TM Trademark of M.T. Deason Company, Inc. © Copyright 2019. All Rights Reserved M.T. Deason Company, Inc. Printed in USA